# STREAMMIND: Unlocking Full Frame Rate Streaming Video Dialogue through Event-Gated Cognition

<sup>1</sup>University of Science and Technology of China <sup>2</sup>Microsoft Research <sup>3</sup> Nanjing University <sup>4</sup> Institute for AI Industry Research (AIR), Tsinghua University

#### **Abstract**

With the rise of real-world human-AI interaction applications, such as AI assistants, the need for Streaming Video Dialogue is critical. To address this need, we introduce STREAMMIND, a video LLM framework that achieves ultra-FPS streaming video processing (100 fps on a single A100) and enables proactive, always-on responses in real time, without explicit user intervention.

To solve the key challenge of the contradiction between linear video streaming speed and quadratic transformer computation cost, we propose a novel perception-cognition interleaving paradigm named "event-gated LLM invocation", in contrast to the existing per-time-step LLM invocation. By introducing a Cognition Gate network between the video encoder and the LLM, LLM is only invoked when relevant events occur. To realize the event feature extraction with constant cost, we propose Event-Preserving Feature Extractor (EPFE) based on state-space method, generating a single perception token for spatiotemporal features. These techniques enable the video LLM with full-FPS perception and real-time cognition response.

Experiments on Ego4D and SoccerNet streaming tasks, as well as standard offline benchmarks, demonstrate state-of-the-art performance in both model capability and real-time efficiency, paving the way for ultra-high-FPS applications, such as Game AI and interactive media. The code and data is available at https://aka.ms/StreamMind.

# 1. Introduction

The advancement of large foundation models is driving an increasing number of real-world human-AI interaction applications, such as AI home companions [3, 41] and human-robot collaboration [54, 63]. These applications heavily rely on streaming video understanding capabili-




Figure 1. The paradigm of existing per-step LLM invocation (left) versus our event-gated LLM invocation (right) for streaming video dialogue task. Our paradigm boosts frame rate up-to 100 fps on A100. ( $R_i$ : response,  $f_i$ : frame, t: time)

ties [14, 26, 44, 61, 71], specifically streaming video dialogue [8, 59]. Streaming video dialogue (StreamingVD) aims to continuously perceive incoming video streams and, based on user queries, provide proactive, real-time, and always-on responses without human intervention. For example, an AI companion could respond to user queries like "Guide me to fix this bicycle" or "Let's watch and discuss the soccer game together".

Streaming video dialogue can be viewed as a generalization of standard offline video dialogue tasks [30, 32, 39, 40, 48, 65, 66], extending video LLMs to broader realworld scenarios. The fundamental challenge of StreamingVD compared to its offline counterpart lies in the requirement for **timing alignment between events and responses**. That is, as the video progresses, the model is required to (1) **proactively decide when to respond and (2) respond in real time before the next event occurs** according to user queries, as illustrated in Fig. 2. However, with current techniques, these two requirements are contradictory and cannot be achieved simultaneously.

The seminal VideoLLM-Online [8] and VideoLLM-MoD [59] introduce a **per-step LLM invocation** paradigm for StreamingVD, shown in Fig. 1. At each time step, it inputs all past frames and the user query to the LLM, to decide when to respond or remain silent. However,

<sup>\*</sup>This work was done during Xin Ding's internship at Microsoft Research.

the  $O(n^3)^1$  computational complexity and limited context window are mismatched with the O(n) frame streaming, making real-time response difficult to achieve. More works [14, 44, 61, 71] focus on enhancing the efficiency of offline video dialogue aiming to meet real-time requirements. However, similar to offline approaches, they depend on user queries to trigger responses rather than the model to do so proactively.

To empower StreamingVD, this paper proposes a new perception-cognition interleaving paradigm, named eventgated LLM invocation, shown in Fig. 1. It is inspired by the event perception mechanism of human brains [68], which states that events are key components of human's perception, attention, and memory<sup>2</sup>. We therefore propose an event-based selective cognition process. Rather than invoking the LLM at every time step, we introduce a Cognition Gate between the video encoder and LLM. The video encoder continuously perceives visual signals of each frame, and only when query-related events occur, the gate will open to invoke the LLM. Analogous to how a text prompt triggers an LLM, streaming visual signals lack a clear stopping point, unlike a finite text sequence. The cognition gate bridges this gap by acting as a mechanism to identify "physical world prompts" for the LLM.

This new paradigm raises two major technical concerns, to achieve both high capability and efficiency. Firstly, existing video encoders in VideoLLMs (e.g., STC in VideoLLAMA) only capture local spatio-temporal features. This results in a linear increase in the number of feature tokens for streaming frames and subsequently a quadratic computation for the processing, failing to meet real-time requirements. Secondly, the Cognition Gate must decide to invoke the LLM or not, based on visual features and the user query. However, only considering efficiency and simply attending visual and query tokens (e.g., Cross Attention in Q-former [28]) limits the gate capability to tasks like featurematching [56, 57] and retrieval [1, 16, 74], struggle to make decisions with deeper semantic understanding.

By addressing the challenges, we realize STREAM-MIND, a novel framework for streamingVD, with the processing speed matching frame rate for the first time. It integrates two techniques. For the video encoder, inspired by the exceptional ability of the state-assisted module [22] in modeling continuous physical signals with constant cost, we propose the *Event-Preserving Feature Extractor* (EPFE) based on the state-assisted module. It generates a single perception token of event features to the gate, resulting in a constant perception cost. For the Cognition Gate, to leverage the world knowledge of LLM while meeting the real-

time requirement, we propose a *Shallow Layer Transfer* method. The Gate is designed to reuse the shallow layers of the LLM and its autoregressive training to maximize the probabilities of "< response/silence >" tokens during training.

To evaluate the performance of the STREAMMIND framework, we adopt evaluation metrics from VideoLLM-Online and a wide range of text generation evaluation metrics. Additionally, we design two novel metrics to comprehensively assess the model's temporal responsiveness. Experiments on real-time Ego4D [21] and SoccerNet [20] demonstrate superior performance across all metrics. Furthermore, our model achieves state-of-the-art results on multiple offline benchmarks, including short- and long-term activity recognition and forecasting on the COIN [52] and Ego4D LTA [24] datasets. Notably, our framework breaks the ultra-FPS streaming video processing bottleneck, enabling streamingVD at up to 100 fps on a single A100 GPU, laying a robust foundation for real-world human-AI interaction applications.

#### 2. Method

#### 2.1. Task Discussion and Definition

**Problem formulation of StreamingVD** Given a video stream  $\mathcal{V}^T:=[v_1,v_2,...,v_T]$  consisting of T frames and a set of queries  $\mathcal{Q}:=\{q_1,q_2,...,q_N\}$ . Traditional video dialogue, shown in Fig. 2, provides a response triggered by a user query. For a query  $q_i$  given at time step  $t_s$ , it responds based on past frames up to time  $t_s(1 < t_s \leq T)$ , regardless of an online or offline scenario. On the other hand, StreamingVD proactively generates responses to a query given at  $t_s$  at any appropriate time steps until the query termination at  $t_e(t_s < t_e \leq T)$ . At each time step  $t_i(t_s \leq t_i \leq t_e)$ , StreaminVD needs to decide whether to generate a response according to the past frames and query, and then generate the response, formulated as follows.

$$\max P(\lceil \operatorname{Res}^{t_i} \rceil \mid \lceil \operatorname{Ctx}^{< t_i} \rceil, \lceil \operatorname{F}^{t_i} \rceil) \tag{1}$$

where  $[\operatorname{Res}^{t_i}] \in \{[\operatorname{Txt}^{t_i}], [\operatorname{EOS}^{t_i}]\}$  means generate a response at a time step  $t_i$ , or remain silence, i.e.,  $[\operatorname{EOS}]$ .  $[\operatorname{Ctx}^{< t_i}]$  denotes the contextual tokens accumulated from past frames and queries before  $t_i$ .  $[\operatorname{F}^{t_i}]$  represents the visual features extracted from the video frame at  $t_i$ .

Challenges of StreamingVD tasks Firstly, increasing number of frames versus real-time requirement. Different from the offline tasks[17, 19, 30, 62, 67], streaming tasks[8, 14, 26, 44, 61, 71] require time alignment between event and response. Besides only accuracy constraint of offline task, streaming video tasks need to consider both accuracy and timeliness constraints. Offline tasks can trade re-

<sup>&</sup>lt;sup>1</sup>Invoking a quadratic-complexity LLM n times results in cubic complexity.

<sup>&</sup>lt;sup>2</sup>A formal definition of an event [68]: "A segment of time at a given location that is conceived by an observer to have a beginning and an end."




Figure 2. Comparison between streaming dialogue (bottom) and traditional dialogue tasks (top). Streaming dialogue proactively generates responses at appropriate time based on user queries and perception, whereas traditional dialogue requires human triggering for each response.

sources and latency for better quality, while streaming task cannot.

Secondly, proactive response versus real-time requirement. Traditional video dialogue [13, 14, 44, 60, 61, 64] are reactive, responding only at the time of user query. However, real-world dialogue is often without human triggering. The user may lack the specific knowledge to formulate questions. Similarly, embodied AI should anticipate user needs rather than merely reacting to commands. However, proactive response means at every frame the model needs to judge, inceasing the model cost by O(n) times.

**Existing works** Conventional offline Video LLMs [10. 32, 33, 35, 72, 73] typically employ a visual encoder [18, 45, 69] and a projection module [28, 39] to process uniformly sampled frames. The output is concatenated with the tokenized question to form a sequence, which is then passed to an LLM decoder to predict a response. However, this approach is impractical for streaming tasks due to the high computational cost associated with processing a large number of frames (T). Therefore, works such as [14, 61]have implemented a sliding-window attention mechanism and a KV-cache system to reduce computational overhead, or incorporated a parallel sampling strategy to enhance processing speed and reduce latency. However, these methods do not proactively trigger response when needed. In contrast, Videollm-Online [8] and MOD [59] utilize the LLM decoder to process every frame of streaming videos, resulting in a cubic computation cost. STREAMMIND, on the other hand, has the potential to process streaming videos at 100 fps, which is crucial for enabling interactive video analysis applications.

#### 2.2. The Overview of STREAMMIND

For a streaming video sequence  $[v^{t_s \leq t_i \leq t_e}]$ , STREAMMIND models the following process as shown in Fig. 3:

1. Perception Phase: With continuous streaming video, each incoming frame v is processed through the CLIP [45] encoder to extract spatial features. The features are then input to our proposed EPFE. EPFE updates its hidden state to correlate the frame's features across temporal dimensions and reduce redundant spatial information. This process generates a new perception token  $[\mathbb{F}^{t_i}_{per}]$  and saves this token in the Perception Memory  $\mathcal{M}^{t_i}_{per}$ . The perception phase can be formulated as follows:

$$[\mathbf{F}_{ner}^{t_i}] = \text{EPFE}(\text{CLIP}(v^{t_i}), \mathbf{H}^{t_i-1}) \tag{2}$$

where  $\mathbf{H}^{t-1}$  denotes the hidden state from the previous time.

**2.** Cognition Gate Judgment: We introduce Cognition Gate  $\mathcal G$  between perception and cognition. The input are user query [Prompt] and the generated perception token  $[\mathbb F^{t_i}_{per}]$  at each time step  $t_i$ . The Cognition Gate learns to determine whether to trigger the cognition phase at  $t_i$ :

$$\max P([\operatorname{Res}^{t_i}] \mid \mathcal{G}([\operatorname{Prompt}], [\operatorname{F}^{t_i}_{per}])) \qquad (3)$$

where  $[Res^{t_i}] \in \{ < /response >, < /silence > \}$  determines whether to trigger a response or remain silent.

**3. Cognition Phase** Upon receiving the trigger signal from the Cognition Gate, STREAMMIND samples perception tokens from the Perception Memory  $\mathcal{M}_{\text{per}}^{t_i}$  to the Cognition Pooling as the input to LLM to generate response.

#### 2.3. Perception Phase

**Motivation:** To match the constant frame rate of streaming videos, ideally the perception phase should be con-




Figure 3. STREAMMIND workflow. For each video frame, the perception stage goes through Clip for spatial features and the proposed EPFE for spatiotemporal features, to generate a single perception token saved in perception memory. The Cognition Gate determines whether to invoke LLM only based on the current perception token. If yes (a query-related event occurs), the tokens in perception memory are sampled to cognition pooling as the input for LLM for cognition response. The gate decouples perception and cognition to enable full-FPS perception and event-based cognition.

stant computation cost for processing each frame. However, current video encoders generally extract local (dozens of frames) spatiotemporal features with constant cost, and input all the generated perception tokens to a transformer model to extract the long-term temporal relationships. The computational cost is  $O(n^3)$ , obviously the lagger behind the streaming rate.

To solve the issue, we propose Event-Preserving Feature Extractor (EPFE) to replace the projection module used in existing video LLMs (e.g., cross-attention and Q-Former). EPFE is based on the SOTA state-space model, i.e., Selective State Space model [22]. As shown in Fig. 3 (blue box) and Eq. 4, for each frame, EPFE dynamically correlates the spatial features and the past internal states to generate a single perception token  $[\mathbb{F}^{t_i}_{per}]$  as well as update its state. This enables a matched speed of streaming video and perception processing, for full FPS Streaming VD.

$$\mathbf{h}_{t+1} = \mathbf{A}\mathbf{h}_t + \mathbf{B}\mathbf{x}_t, \quad \mathbf{y}_t = \mathbf{C}\mathbf{h}_t \tag{4}$$

where  $\mathbf{A}, \mathbf{B}$ , and  $\mathbf{C}$  are learnable state-space matrices for state, input, and output, respectively.  $\mathbf{x_t}$  is the input frame of the current time step.  $\mathbf{h_t}$  is the internal hidden state.  $\mathbf{y_t}$  is the output, i.e., perception token.

Benefit from the strong temporal modeling capability of Selective SSM, our EPFE with only 56 M parameters can learn long-term event-level spatiotemporal features with constant cost. As Appendix Fig. 1 illustrates, perception tokens generated by EPFE can distinguish different events and noise frames, while maintaining a state of the event. Even after unrelated noise frames, the perception tokens are capable of refocusing on the event.

# 2.4. Cognition Gate

**Motivation:** Cognition Gate needs to determine whether to invoke LLM in real-time, based on the current perception

token and user query. For example, during the soccer match, some user query may only care LLM response for scoring moments, while others may need detailed tactical analysis.

However, we find it highly challenging. For real-time consideration, we first employ a simple Transformer block with cross-attention to associate the user query with the visual encoder's output for trigger decisions. However, it struggles to make accurate judgments at the right time step, as shown in Tab.6. We identify two key reasons for this:

1) The Cognition Gate only has access to information up to the current step, lacking a global temporal perspective for decision-making. 2) User queries may not directly correspond to specific video frames in a retrieval-like manner (e.g., guide me to repair a bicycle or cooking).

Therefore, the Cognition Gate requires the world knowledge of LLMs. However, due to the size of LLMs, even processing a single perception token as input incurs a high computational cost. Notably, the Gate only needs to generate a response/silence token for a single iteration.

To achieve it, We propose the Shallow Layer Transfer method, which initializes the Gate using the early layers of the LLM and then fine-tunes it in a supervised autoregressive manner with the StreamVD dataset. As shown in Sec. 5.2, we conducted extensive experiments to analyze its impact. The results indicate that the first few layers exhibit slight variations in behavior, allowing for scalability based on requirements. In this work, we use four layers.

#### **2.5. The Training Strategy of STREAMMIND**

**Model Architecture** As illustrated in Figure 3, the STREAMMIND video LLM integrates CLIP [45], EPFE, Cognition Gate, and the LLM. CLIP is the pre-trained spatial feature extractor. EPFE then takes the spatial features as input as well as its internal state to extract spatiotemporal features and generate a perception token. Cognition Gate

then evaluates the current perception token and user query to determine whether to invoke LLM. To achieve this, it is needed to train EPFE, Cognition Gate, and also align the representation space of EPFE and LLM, as shown in Fig. 4.

**Algorithm 1:** Streaming Video Dataset Construction

```
Require: Offline video dataset C = \{c_i, t_i\}_{i=1}^n (c_i):
    caption at time t_i).
Ensure: Dataset D with captions meeting StreamVD
    requirements and Cognition Gate labels.
 1: Step 1: Preprocessing
 2: D \leftarrow [], cap \leftarrow c_1, time \leftarrow t_s
 3: for i = 2 to n do
       if c_i \neq cap then
 5:
         Append (cap, time) to D
 6:
         cap \leftarrow c_i, time \leftarrow t_i
       end if
 7:
 8: end for
 9: Append (cap, time) to D
10: Step 2: Silence-Response Labeling
11: for each frame f between d_i and d_{i+1} do
       Label f with </response> if captioned, else
       </silence>
13: end for
14: return D
```

**Data Preparation** Streaming datasets are constructed by processing existing offline datasets. Streaming VD tasks require the model to response as early as possible when relevant events occur while avoid redundant responses. To achieve this, we eliminate repetitive captions from the offline datasets and transform them into streaming datasets using the following methods, detailed in Algorithm 1.

- Preprocessing: Adjacent identical captions are merged, with the timestamp of the first occurrence being recorded as the annotation point for the caption.
- Silence-Response Labeling: To train the Cognition Gate, we insert < /silence > tokens into video frames between two adjacent captions. These tokens act as indicators to guide the Cognition Gate in generating the < /silence >. The initial frame corresponding to captioned events is labeled with the < /response > token.

**Training Strategy** We adopt a two-stage training strategy, as shown in Fig. 4. In contrast to previous typical two-stage training approaches [29, 40, 70], our method uses a dedicated stage for Cognition Gate. In the first stage, the LLM and EPFE are jointly trained using video frames and captions from the streaming dataset, ensuring spatiotemporal feature alignment with the LLM. The second stage

trains only the Cognition Gate, which is initialized from the shallow layers of the LLM. This training also follows the LLM autoregressive manner to generate </silence> or </response> tokens, determining whether to invoke the LLM. Since the response label is much sparser than silence (e.g. 310:1), we introduce a balancing weight into the standard Cross Entropy loss during training to balance the labels. Refer to Sec. 3.1 and Appendix Sec. 1 for more training details.




Figure 4. The two-stage training process of STREAMMIND. In the first stage, the EPFE spatiotemporal extractor and the LLM are jointly trained to align their representations. In the second stage, the Cognition module is trained to generate response/silence tokens. Both stages follow a supervised autoregressive training approach for language modeling.

# 3. Experiment

# 3.1. Experimental Settings

**Baseline and Datasets** Since existing works focusing on streamingVD [8, 26, 59], except for VideoLLM-Online [8], do not provide open-source data or training methods, to demonstrate our outstanding performance, we re-implemented all previous works (VideoLLM-Online [8] and VideoLLM-MOD [59]) in the StreamingVD domain as baselines, using consistent settings across all experiments.

For dataset selection, since the Ego4D dataset [21] is inherently collected in a streaming manner, containing various queries, real-time responses, and narrations, and has been used as an main evaluation dataset in works [8, 31, 59], we selected it as one of our evaluation datasets. Furthermore, to further demonstrate the effectiveness of our approach on long videos, we also conducted experiments on the SoccerNet-Caption dataset [20]. This dataset includes 471 complete soccer match videos with a total duration of 715 hours, where each video is approximately 45 minutes long and provides commentary at appropriate timestamps.

**Implementation Details:** Model training was conducted on videos sampled at 2 fps, using 8 NVIDIA A100 GPUs. Each stage of the training process was conducted for one epoch. To optimize the learning rate, we applied the CosineAnnealingLR scheduler, with learning rates set to 2e-5 and 2e-6 respectively. Additionally, specific techniques were applied to the design of the Cognition Gate and

Table 1. Online Experiments Results.

DataSet	Method	Timing Alig	nment ↑	Language Modeling Capability ↑			Training Cost	
Dataset	Wiethod	TriggerAcc	TimVal	BLUE-1	BLUE-4	METEOR	ROUGE-L	Training Cost
	VideoLLM-Online	32.34%	29.66%	66.01	35.25	31.12	63.06	24h
Ego4d	VideoLLM-MoD	32.36%	29.65%	65.34	35.21	30.65	63.02	14h
	Ours	43.34%	39.73%	67.12	39.26	31.60	65.71	(11+8)h
	VideoLLM-Online	31.25%	28.34%	75.36	64.23	50.92	81.57	12h
Soccer	VideoLLM-MoD	31.24%	28.12%	74.96	64.18	50.24	81.59	7h
	Ours	52.18%	47.36%	82.78	66.70	51.43	82.04	(5+3)h

Table 2. Online Experiments Results. LION-FS was released on arXiv just two days before our submission, but its code was not released. Therefore, we could only obtain the Ego4D results based on its paper.

DataSet	Method	TimeDiff ↓	Fluency ↑	PPL ↓	Correctiness ↑
	VideoLLM-Online	2.04	45.0%	2.43	48.1%
F 4.1	VideoLLM-MOD	2.04	45.2%	2.41	48.9%
Ego4d	LION-FS	2.15	46.1%	2.09	52.4%
	Ours	1.89	60.2%	2.02	77.3%
	VideoLLM-Online	15.62	46.35%	1.79	53.5%
Soccer	VideoLLM-MOD	15.68	45.34%	1.80	53.3%
	Ours	14.02	70.35%	1.59	89.2%

Table 3. Results on COIN benchmarks(left to right): step recognition, task recognition, next forecasting, procedure forecasting, procedure forecasting with a goal.

Method	Not use	COIN	COIN Benchmark Top-1 Accuracy ↑				
Method	HT 100M	Step	Task	Next	Proc	Proc.+	
ClipBERT	<b>√</b>	30.8	65.4	-	-	-	
TimeSformer	×	46.5	85.3	34.0	17.0	40.1	
Paprika	×	51.0	85.8	43.2	-	-	
DistantSup	×	54.1	90.0	39.4	-	-	
VideoTF	×	56.5	91.0	42.4	40.2	46.4	
ProcedureVRL	×	56.9	90.8	46.8	-	-	
VideoTaskGraph	×	57.2	90.5	40.2	-	-	
VideoLLM-online-7B-v1	✓	59.8	92.1	48.1	47.9	52.9	
VideoLLM-online -8B-v1+	✓	63.1	92.7	49.1	49.8	54.1	
VideoLLM-MOD	✓	63.4	92.8	49.7	49.8	53.3	
Ours	✓	63.7	93.2	49.9	49.8	54.2	

Table 4. Results on Ego4DLTA benchmark, evaluated on public server. ED@Z=20 denotes editing distance for future 20 actions.

Method	Not use			D LTA ED	D@Z=20	
Wichiod	Ego VLP	-End?	Verb ↓	Noun ↓	Action ↓	
CLIP	<b>√</b>	<b>√</b>	0.739	0.769	0.941	
EgoT2	✓	✓	0.722	0.764	0.935	
I-CVAE	✓	✓	0.753	0.749	0.931	
HierVL	✓	✓	0.724	0.735	0.928	
VideoLLM	×	✓	0.721	0.725	0.921	
VideoLLM-online-7B-v1	✓	✓	0.697	0.698	0.897	
VideoLLM-online-8B-v1+	✓	✓	0.689	0.671	0.884	
VideoLLM-MOD	✓	✓	0.689	0.676	0.884	
Ours	✓	✓	0.689	0.655	0.881	

methods to address the imbalance in the Silence-Response ratio, which are detailed in Section 5.

#### 3.2. Evaluate Metrics

To evaluate the effectiveness of STREAMMIND, we focus on assessing its **Timing Alignment** Capability and **Language Modeling** Capability. Existing evaluation metrics include LM-PPL (Language Modeling Perplexity) and LM-Correctness, which evaluate language modeling accuracy at specific timestamps. Additionally, the Time Difference (TimeDiff) metric is used to measure the temporal alignment of responses in an streaming video LLM, while the Fluency metric aims to provide a holistic evaluation of both linguistic quality and temporal consistency.

However, these metrics have several limitations:

- LM-PPL and LM-Correctness focus solely on the exact alignment between model outputs and reference narrations, ignoring aspects such as synonym substitutions, sentence fluency, and the ability to capture critical information.
- TimeDiff, as a metric for timing alignment Capability, evaluates temporal alignment only within a single dialogue turn. It does not assess the Cognition Gate's overall decision-making across the entire video stream.

To address these limitations, we introduce the following metrics:

- Trigger Accuracy (TriggerAcc): To evaluate whether the streaming video LLM responds at the correct time steps during entire streaming video.
- Timing Validity (TimVal): To comprehensively evaluate whether the streaming video LLM consistently makes the correct decisions throughout the streaming video—speaking when necessary and remaining silent when appropriate.
- BLUE [42], METEOR [2], ROUGE-L [34]: Widely used evaluation metrics in the field of text generation [6, 9, 38] and image narration [7, 43, 47], which fully consider factors such as synonym matching, stemming, word order, and key semantic expressions. These metrics enable a comprehensive assessment of dialogues in the StreamingVD process.

# 3.3. Comprehensive Evaluation on Streaming and Offline Video

Online Experiments: We compared our model with all existing streaming dialogue models [8, 31, 59] in Tab 1 and Tab 2. Under comparable training costs, experiments on real-time Ego4D and SoccerNet demonstrate superior performance across all metrics. Additionally, STREAMMIND can process video streams at a 10× higher FPS. This improvement is attributed to the event-level modeling capability of EPFE and the strong timing alignment capability of the cognition gate in the perception stage, which together provide the LLM in the cognition phase with a concise yet comprehensive representation.

Offline Experiments: We also leveraged the COIN [52] and Ego4D LTA [24] benchmark to demonstrate STREAM-MIND effectiveness in traditional offline video scenarios, covering six common benchmarks: step recognition, step forecasting, task summarization, procedure forecasting, and procedure forecasting with a goal. As shown in Tab 3 and Tab 4, our approach achieves state-of-the-art performance across all tasks.

#### 3.4. Real-time Inference Efficiency

Standard frame rates for films are typically 24 FPS, which is considered the minimum requirement for smooth motion perception. In contrast, games often operate at much higher frame rates, ranging from 30 FPS to over 100 FPS, to ensure a immersive experience. To validate the real-time performance of STREAMMIND, we conducted inference efficiency evaluations on NVIDIA A100 and H100 GPUs.

Specifically, we compared VideoLLM-Online, VideoLLM-MOD, and STREAMMIND by measuring their actual processing time for 1-second video across input frame rates from 5 to 100 FPS. As shown in Figure 6, a processing time under 1 second indicates real-time performance without disrupting playback.

The results reveal that VideoLLM-Online and VideoLLM-MOD struggle to process video streams beyond 10 FPS, leading to potential latency issues in real-world applications. In contrast, our method achieves true real-time performance, efficiently handling both standard film/TV frame rates and high-refresh gaming scenarios up to 100 FPS, ensuring real-time responses.

#### 4. Perception Phase Visualization Experiment

To visualize the perception phase, we conducted the following experiment: As streaming video inputs continued, we preserved all perception tokens generated by the Cognition Gate between two consecutive cognition phases. We then computed the cosine similarity between these tokens to analyze their consistency over time. The results indicate that perception tokens generated by EPFE can effectively distinguish between relevant and irrelevant events while maintaining a strong memory of the primary event. Even after encountering unrelated events, the perception tokens are capable of refocusing on the main event. Furthermore, throughout the entire event, perception tokens exhibit robust memory retention, maintaining a high similarity with earlier stages of the event even in later phases, as shown in figure.5.(a).

We repeated this experiment on STC, as shown in figure 5.(b), but its perception tokens failed to maintain long-term feature similarity, capturing only local spatiotemporal features. This further highlights the superiority of EPFE in preserving event-level semantics over extended video sequences.

#### 5. Ablation

#### 5.1. Impact of Silence-Response Sample Imbalance

As described in the data preparation process, during the Silence-Response Labeling stage, the dataset inherently exhibits a severe imbalance in the Silence-Response ratio. For example, in a 1-minute video at 30 FPS, if only 5 frames require a response, the silence-response ratio becomes 360:1. Such an extreme imbalance can significantly impact the training process.

To mitigate this issue, we introduce a balancing weight  $W_s$  into the standard Cross Entropy (CE) loss during training, where  $W_s$  and  $1-W_s$  represent the weights for silence and response, respectively. We conducted extensive ablation studies on Silence-Response sample balancing based on the weight  $W_s$ . The results indicate that, compared to the standard cross-entropy loss,  $W_s$  significantly improves the final performance. However, an unfortunate observation is that the optimal  $W_s$  varies considerably, even differing by orders of magnitude. To address this, we analyzed the ratio P of </silence> to </re> / response> tokens in the Ego4D and SoccerNet datasets, which are <math>310:1 and 71:1, respectively. Based on these observations, we derive an empirical formula for the optimal balancing weight  $W_s^{\rm opt}$ :

$$W_s^{\text{opt}} \approx 10P$$
 (5)

### 5.2. The Ablation of Cognition Gate

The Cognition Gate plays a crucial role throughout the perception-cognition interleaving process. We conducted detailed ablation experiments to analyze its impact.

The Architecture of Cognition Gate The structure of the gate directly determines its capabilities. To this end, we constructed multiple classification networks using MLP projectors, Cross-Attention, and Transformers. [53] Additionally, we built a set of autoregressive networks using an




Figure 5. A cosine similarity heatmap of frames across two consecutive events.




Figure 6. Comparison of running time for processing 1 second of streaming video frames using different methods on A100 (Top) and H100 (Bottom).

LLM block. The results are shown in Tab.6. It is evident that the LLM-like structure achieved better performance. For a detailed analysis, please refer to Section 2.4.

**Initialization Strategies** We investigate three initialization strategies for the Cognition Gate to enhance its effectiveness: (i) Random Initialization: All layers are initialized from a standard random distribution without utilizing prior knowledge from the LLM. (ii) SkipBlock Initialization: The

Table 5. Perceptive Judgement Capability

Datasets	Method	TimeDiff ↓	TriggerAcc ↑	TimVal ↑
	Standard CE	2.05	31.37%	30.91%
	0.10	1.92	41.34%	37.60%
Ess4D	0.12	1.88	42.16%	38.63%
Ego4D	0.15	1.89	43.34%	39.73%
	0.17	1.95	40.23%	39.44%
	0.20	1.97	35.35%	34.60%
	Standard CE	15.89	31.34%	29.61%
	0.01	14.33	50.35%	41.32%
Soccer	0.02	14.35	51.62%	44.8%
Soccei	0.03	14.02	52.18%	47.36%
	0.04	14.03	44.69%	42.37%
	0.05	14.12	41.22%	39.82%

Table 6. Ablation Study on the architecture of cognition gate

Architecture	TimeDiff ↓	TriggerAcc ↑	TimVal ↑
Linear Layer	5.06	20.13%	17.65%
MLP projector + Linear	4.34	21.75%	18.33%
Transformers + Linear	3.78	21.58%	18.97%
Cross-Attention + Linear	3.64	24.34%	20.36%
Single LLM block	2.22	35.35%	32.11%

Cognition Gate is initialized by uniformly selecting layers from the LLM, with the number of skipped layers determined by the ratio of the Cognition Gate's depth to the total number of LLM layers. (iii) EarlyBlock Initialization: The first few layers of the LLM are directly used to initialize the Cognition Gate, leveraging the LLM's early-stage processing capabilities.

**Number of Blocks** The Cognition Gate consists of multiple layers, and its depth plays a crucial role in balancing computational efficiency and perceptual accuracy.

The results in Tab.7 and Tab.8 show that fine-tuning the

Table 7. Ablation Study on the Strategy of Initialization

Strategy of Initialization	TimeDiff ↓	TriggerAcc ↑	TimVal ↑
Random	2.10	39.65%	37.35%
SkipBlock	1.89	40.23%	37.67%
EarlyBlock	1.89	43.34%	39.73%

Table 8. Ablation Study on the Strategy of Initialization

#Num of Block	TimeDiff ↓	TriggerAcc ↑	TimVal ↑
2	1.92	41.53%	37.65%
3	1.90	42.35%	38.34%
4	1.89	43.34%	39.73%
5	1.88	42.67%	38.56%
6	1.89	42.56%	38.34%

shallow layers of the LLM yields the best performance. We attribute this to the fact that gate operates within a limited decision space (binary: Yes/No), making deeper layers—primarily responsible for nuanced language generation—unnecessary. Thus, we propose the Shallow Layer Transfer method to construct the Cognition Gate, as detailed in Section 2.4.

# **5.3.** The performance of Event-preserving Feature extractor

To evaluate the role of EPFE in the perception phase, we compare it with commonly used extractors in VideoLLMs, including: 1) The Q-Former [28]. 2) The Spatial-Temporal Convolution Connector (STC Connector) [12], which has demonstrated outstanding performance in videollm and has been widely adopted [29, 58, 70]. Notably, STC employs 3D convolution for spatial-temporal aggregation. To preserve local visual patterns during spatial compression, it follows work [5] by incorporating a RegStage block [46] before and after the 3D convolution, which has been shown to enhance spatial understanding. Experimental results indicate that EPFE achieves superior performance.

Table 9. Perceptive Judgement Capability

Method	TimeDiff ↓	TriggerAcc ↑	TimVal ↑
Q-former	3.78	26.65 %	25.31%
STC	3.56	27,54%	26.87%
EPFE	1.89	43.34%	39.73%

# 6. Related Work

#### 6.1. Offline VideoLLMs.

In recent years, there has been a surge of interest in leveraging Large Language Models (LLMs) for video understanding, leading to the development of offline videoLLMs. The biggest challenge for it is managing memory requirements [4, 11, 15, 23, 49, 50] and compressing redundant frame features [12, 25, 27, 51, 75]. LaViLa [37] addresses

this challenge by transforming LLMs into narrators that generate detailed descriptions of long videos from visual inputs. Other models, such as ChatVideo [55] and MM-VID [36], convert videos into text to improve comprehension. MovieChat [49], on the other hand, combines all frame features using a simple averaging strategy. However, in the context of online streaming, there has been limited exploration into how VideoLLMs can meet the demands of temporal alignment and real-time processing for streaming video inputs.

#### 6.2. Online VideoLLMs.

Recent studies have introduced VideoLLMs specifically designed for online stream understanding, while most existing works [14, 44, 61, 71, 76] focus on improving offline video efficiency to meet real-time requirements. However, they fail to proactively decide when to respond based on user requirements. For example, ReKV [14] implemented a sliding-window attention mechanism and a KV-cache system to reduce computational overhead. To address this, VideoLLM-Online [8] introduces per-step LLM invocation for online video dialogue, as shown in Fig.1. However, its performance is constrained by limited per-frame processing capability due to the absence of effective frame compression strategies. VideoLLM-MOD [59] mitigates this issue by incorporating a mixture-of-depth approach for efficient visual token computation, enabling higher visual input resolutions. Building on MOD, LION-FS [31] proposes Token Aggregation Router and Token Dropping Router as the Fast Path, adaptively aggregating distinct features while discarding redundant ones. However, they remain limited to processing videos at only 10 FPS.

Overall, prior work remains restricted by the contradiction between sequential full-frame processing and the extremely high efficiency requirements of streaming video, lacking breakthrough paradigm designs explicitly suited for streaming frame inputs. To address these challenges, our approach introduces a novel perception-cognition interleaving paradigm and proposes the STREAMMIND framework, enabling VideoLLM to achieve proactive responses and real-time streaming video understanding, with a maximum throughput of up to 100 FPS.

#### 7. Visualization of demo

we show an illustrative snippet of StreamingVD on a live football match. The query at the beginning is: "Hey, Robot, can you watch the football game with me and provide commentary?",as show in figure 7.

#### 8. Conclusion

In this paper, we introduce a novel perception-cognition interleaving paradigm called "event-gated LLM invocation"



Figure 7. An illustrative snippet of Streaming VD on a live football match. The query at the beginning is: "Hey, Robot, can you watch the football game with me and provide commentary?"

and propose the STREAMMIND framework, addressing the contradiction between sequential full-frame processing and the extremely high efficiency requirements of streaming video. As a result, STREAMMIND can process video at up to 100 FPS, achieving the SOTA performance across all existing metrics and benchmarks.

#### References

- [1] Roberto Amoroso, Gengyuan Zhang, Rajat Koner, Lorenzo Baraldi, Rita Cucchiara, and Volker Tresp. Perceive, query & reason: Enhancing video qa with question-guided temporal queries. arXiv preprint arXiv:2412.19304, 2024. 2
- [2] Satanjeev Banerjee and Alon Lavie. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization, pages 65–72, 2005. 6
- [3] Pietro Battistoni, Andrea Antonio Cantone, Mariarosaria Esposito, Rita Francese, Francesca Pia Perillo, Marco Romano, Monica Sebillo, and Giuliana Vitiello. Using artificial intelligence and companion robots to improve home health-care for the elderly. In *International Conference on Human-Computer Interaction*, pages 3–17. Springer, 2023. 1
- [4] Jiarui Cai, Mingze Xu, Wei Li, Yuanjun Xiong, Wei Xia, Zhuowen Tu, and Stefano Soatto. Memot: Multi-object tracking with memory. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 8090–8100, 2022. 9

- [5] Junbum Cha, Wooyoung Kang, Jonghwan Mun, and Byungseok Roh. Honeybee: Locality-enhanced projector for multimodal llm. In *Proceedings of the IEEE/CVF Con*ference on Computer Vision and Pattern Recognition, pages 13817–13827, 2024. 9
- [6] Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, et al. A survey on evaluation of large language models. ACM transactions on intelligent systems and technology, 15(3):1–45, 2024. 6
- [7] Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pretraining to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3558–3568, 2021. 6
- [8] Joya Chen, Zhaoyang Lv, Shiwei Wu, Kevin Qinghong Lin, Chenan Song, Difei Gao, Jia-Wei Liu, Ziteng Gao, Dongxing Mao, and Mike Zheng Shou. Videollm-online: Online video large language model for streaming video. In *Proceedings of* the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 18407–18418, 2024. 1, 2, 3, 5, 7, 9
- [9] Zixiang Chen, Yihe Deng, Huizhuo Yuan, Kaixuan Ji, and Quanquan Gu. Self-play fine-tuning converts weak language models to strong language models. *arXiv preprint* arXiv:2401.01335, 2024. 6
- [10] Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Pro-*

- ceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 24185–24198, 2024. 3
- [11] Ho Kei Cheng and Alexander G Schwing. Xmem: Long-term video object segmentation with an atkinson-shiffrin memory model. In *European Conference on Computer Vision*, pages 640–658. Springer, 2022. 9
- [12] Zesen Cheng, Sicong Leng, Hang Zhang, Yifei Xin, Xin Li, Guanzheng Chen, Yongxin Zhu, Wenqi Zhang, Ziyang Luo, Deli Zhao, et al. Videollama 2: Advancing spatial-temporal modeling and audio understanding in video-llms. arXiv preprint arXiv:2406.07476, 2024. 9
- [13] Shangzhe Di and Weidi Xie. Grounded question-answering in long egocentric videos. In *Proceedings of the IEEE/CVF* Conference on Computer Vision and Pattern Recognition, pages 12934–12943, 2024. 3
- [14] Shangzhe Di, Zhelun Yu, Guanghao Zhang, Haoyuan Li, Hao Cheng, Bolin Li, Wanggui He, Fangxun Shu, Hao Jiang, et al. Streaming video question-answering with in-context video kv-cache retrieval. In *The Thirteenth International Conference on Learning Representations*. 1, 2, 3, 9
- [15] Yue Fan, Xiaojian Ma, Rujie Wu, Yuntao Du, Jiaqi Li, Zhi Gao, and Qing Li. Videoagent: A memory-augmented multimodal agent for video understanding. In *European Conference on Computer Vision*, pages 75–92. Springer, 2024.
- [16] Feiteng Fang, Yuelin Bai, Shiwen Ni, Min Yang, Xiaojun Chen, and Ruifeng Xu. Enhancing noise robustness of retrieval-augmented language models with adaptive adversarial training. arXiv preprint arXiv:2405.20978, 2024. 2
- [17] Xinyu Fang, Kangrui Mao, Haodong Duan, Xiangyu Zhao, Yining Li, Dahua Lin, and Kai Chen. Mmbench-video: A long-form multi-shot benchmark for holistic video understanding. Advances in Neural Information Processing Systems, 37:89098–89124, 2025. 2
- [18] Yuxin Fang, Wen Wang, Binhui Xie, Quan Sun, Ledell Wu, Xinggang Wang, Tiejun Huang, Xinlong Wang, and Yue Cao. Eva: Exploring the limits of masked visual representation learning at scale. In *Proceedings of the IEEE/CVF con*ference on computer vision and pattern recognition, pages 19358–19369, 2023. 3
- [19] Chaoyou Fu, Yuhan Dai, Yongdong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, et al. Video-mme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. *arXiv* preprint arXiv:2405.21075, 2024. 2
- [20] Silvio Giancola, Mohieddine Amine, Tarek Dghaily, and Bernard Ghanem. Soccernet: A scalable dataset for action spotting in soccer videos. In *Proceedings of the IEEE confer*ence on computer vision and pattern recognition workshops, pages 1711–1721, 2018. 2, 5
- [21] Kristen Grauman, Andrew Westbury, Eugene Byrne, Zachary Chavis, Antonino Furnari, Rohit Girdhar, Jackson Hamburger, Hao Jiang, Miao Liu, Xingyu Liu, et al. Ego4d: Around the world in 3,000 hours of egocentric video. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 18995–19012, 2022. 2,

- [22] Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. CoRR, abs/2312.00752, 2023. 2, 4
- [23] Bo He, Hengduo Li, Young Kyun Jang, Menglin Jia, Xuefei Cao, Ashish Shah, Abhinav Shrivastava, and Ser-Nam Lim. Ma-lmm: Memory-augmented large multimodal model for long-term video understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13504–13514, 2024. 9
- [24] Daoji Huang, Otmar Hilliges, Luc Van Gool, and Xi Wang. Palm: Predicting actions through language models@ ego4d long-term action anticipation challenge 2023. *arXiv preprint arXiv:2306.16545*, 2023. 2, 7
- [25] De-An Huang, Shijia Liao, Subhashree Radhakrishnan, Hongxu Yin, Pavlo Molchanov, Zhiding Yu, and Jan Kautz. Lita: Language instructed temporal-localization assistant. In European Conference on Computer Vision, pages 202–218. Springer, 2024. 9
- [26] Zhenpeng Huang, Xinhao Li, Jiaqi Li, Jing Wang, Xiangyu Zeng, Cheng Liang, Tao Wu, Xi Chen, Liang Li, and Limin Wang. Online video understanding: A comprehensive benchmark and memory-augmented method. arXiv preprint arXiv:2501.00584, 2024. 1, 2, 5
- [27] Yang Jin, Zhicheng Sun, Kun Xu, Liwei Chen, Hao Jiang, Quzhe Huang, Chengru Song, Yuliang Liu, Di Zhang, Yang Song, et al. Video-lavit: Unified video-language pre-training with decoupled visual-motional tokenization. arXiv preprint arXiv:2402.03161, 2024. 9
- [28] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730–19742. PMLR, 2023. 2, 3, 9
- [29] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. arXiv preprint arXiv:2305.06355, 2023. 5, 9
- [30] Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, et al. Mvbench: A comprehensive multi-modal video understanding benchmark. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 22195— 22206, 2024. 1, 2
- [31] Wei Li, Bing Hu, Rui Shao, Leyang Shen, and Liqiang Nie. Lion-fs: Fast & slow video-language thinker as online video assistant. arXiv preprint arXiv:2503.03663, 2025. 5, 7, 9
- [32] Yanwei Li, Chengyao Wang, and Jiaya Jia. Llama-vid: An image is worth 2 tokens in large language models. In *European Conference on Computer Vision*, pages 323–340. Springer, 2024. 1, 3
- [33] Bin Lin, Yang Ye, Bin Zhu, Jiaxi Cui, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united visual representation by alignment before projection. *arXiv preprint* arXiv:2311.10122, 2023. 3
- [34] Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81, 2004. 6

- [35] Ji Lin, Hongxu Yin, Wei Ping, Pavlo Molchanov, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 26689–26699, 2024. 3
- [36] Kevin Lin, Faisal Ahmed, Linjie Li, Chung-Ching Lin, Ehsan Azarnasab, Zhengyuan Yang, Jianfeng Wang, Lin Liang, Zicheng Liu, Yumao Lu, et al. Mm-vid: Advancing video understanding with gpt-4v (ision). arXiv preprint arXiv:2310.19773, 2023. 9
- [37] Xingyu Liu, Joon-Young Lee, and Hailin Jin. Learning video representations from correspondence proposals. In *Proceedings of the IEEE/CVF conference on Computer Vision and Pattern Recognition*, pages 4273–4281, 2019. 9
- [38] Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: Nlg evaluation using gpt-4 with better human alignment. *arXiv preprint* arXiv:2303.16634, 2023. 6
- [39] Ruipu Luo, Ziwang Zhao, Min Yang, Junwei Dong, Da Li, Pengcheng Lu, Tao Wang, Linmei Hu, Minghui Qiu, and Zhongyu Wei. Valley: Video assistant with large language model enhanced ability. arXiv preprint arXiv:2306.07207, 2023. 1, 3
- [40] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. arXiv preprint arXiv:2306.05424, 2023. 1, 5
- [41] Kelly Merrill Jr, Jihyun Kim, and Chad Collins. Ai companions for lonely individuals and the role of social presence. *Communication Research Reports*, 39(2):93–103, 2022. 1
- [42] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318, 2002. 6
- [43] Jordi Pont-Tuset, Jasper Uijlings, Soravit Changpinyo, Radu Soricut, and Vittorio Ferrari. Connecting vision and language with localized narratives. In *Computer Vision–ECCV* 2020: 16th European Conference, Glasgow, UK, August 23– 28, 2020, Proceedings, Part V 16, pages 647–664. Springer, 2020. 6
- [44] Rui Qian, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Shuangrui Ding, Dahua Lin, and Jiaqi Wang. Streaming long video understanding with large language models. *Advances in Neural Information Processing Systems*, 37:119336–119360, 2025. 1, 2, 3, 9
- [45] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021. 3, 4
- [46] Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 10428–10436, 2020. 9

- [47] Jiayuan Rao, Haoning Wu, Chang Liu, Yanfeng Wang, and Weidi Xie. Matchtime: Towards automatic soccer game commentary generation. arXiv preprint arXiv:2406.18530, 2024. 6
- [48] Shuhuai Ren, Linli Yao, Shicheng Li, Xu Sun, and Lu Hou. Timechat: A time-sensitive multimodal large language model for long video understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14313–14323, 2024. 1
- [49] Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng Zhang, Haoyang Zhou, Feiyang Wu, Haozhe Chi, Xun Guo, Tian Ye, Yanting Zhang, et al. Moviechat: From dense token to sparse memory for long video understanding. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 18221–18232, 2024. 9
- [50] Larry R Squire, Lisa Genzel, John T Wixted, and Richard G Morris. Memory consolidation. *Cold Spring Harbor per*spectives in biology, 7(8):a021766, 2015. 9
- [51] Guangzhi Sun, Wenyi Yu, Changli Tang, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang. Finegrained audio-visual joint representations for multimodal large language models. arXiv preprint arXiv:2310.05863, 2023. 9
- [52] Yansong Tang, Dajun Ding, Yongming Rao, Yu Zheng, Danyang Zhang, Lili Zhao, Jiwen Lu, and Jie Zhou. Coin: A large-scale dataset for comprehensive instructional video analysis. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 1207– 1216, 2019. 2, 7
- [53] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. Advances in neural information processing systems, 30, 2017. 7
- [54] Ales Vysocky and Petr Novak. Human-robot collaboration in industry. MM Science Journal, 9(2):903–906, 2016.
- [55] Junke Wang, Dongdong Chen, Chong Luo, Xiyang Dai, Lu Yuan, Zuxuan Wu, and Yu-Gang Jiang. Chatvideo: A tracklet-centric multimodal and versatile video understanding system. arXiv preprint arXiv:2304.14407, 2023. 9
- [56] Qing Wang, Jiaming Zhang, Kailun Yang, Kunyu Peng, and Rainer Stiefelhagen. Matchformer: Interleaving attention in transformers for feature matching. In *Proceedings of the Asian Conference on Computer Vision*, pages 2746–2762, 2022. 2
- [57] Xunguang Wang, Zhenlan Ji, Pingchuan Ma, Zongjie Li, and Shuai Wang. Instructta: Instruction-tuned targeted attack for large vision-language models. arXiv preprint arXiv:2312.01886, 2023. 2
- [58] Yuxuan Wang, Yueqian Wang, Pengfei Wu, Jianxin Liang, Dongyan Zhao, and Zilong Zheng. Lstp: Language-guided spatial-temporal prompt learning for long-form video-text understanding. *arXiv e-prints*, pages arXiv–2402, 2024. 9
- [59] Shiwei Wu, Joya Chen, Kevin Qinghong Lin, Qimeng Wang, Yan Gao, Qianli Xu, Tong Xu, Yao Hu, Enhong Chen, and Mike Zheng Shou. Videollm-mod: Efficient videolanguage streaming with mixture-of-depths vision computation. Advances in Neural Information Processing Systems, 37:109922–109947, 2025. 1, 3, 5, 7, 9

- [60] Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. Next-qa: Next phase of question-answering to explaining temporal actions. In *Proceedings of the IEEE/CVF con*ference on computer vision and pattern recognition, pages 9777–9786, 2021. 3
- [61] Haomiao Xiong, Zongxin Yang, Jiazuo Yu, Yunzhi Zhuge, Lu Zhang, Jiawen Zhu, and Huchuan Lu. Streaming video understanding and multi-round interaction with memoryenhanced knowledge. arXiv preprint arXiv:2501.13468, 2025. 1, 2, 3, 9
- [62] Dejing Xu, Zhou Zhao, Jun Xiao, Fei Wu, Hanwang Zhang, Xiangnan He, and Yueting Zhuang. Video question answering via gradually refined attention over appearance and motion. In *Proceedings of the 25th ACM international conference on Multimedia*, pages 1645–1653, 2017. 2
- [63] Lin Xu, Yilin Zhao, Daquan Zhou, Zhijie Lin, See Kiong Ng, and Jiashi Feng. Pllava: Parameter-free llava extension from images to videos for video dense captioning. arXiv preprint arXiv:2404.16994, 2024.
- [64] Antoine Yang, Antoine Miech, Josef Sivic, Ivan Laptev, and Cordelia Schmid. Just ask: Learning to answer questions from millions of narrated videos. In *Proceedings of* the IEEE/CVF international conference on computer vision, pages 1686–1697, 2021. 3
- [65] Antoine Yang, Antoine Miech, Josef Sivic, Ivan Laptev, and Cordelia Schmid. Zero-shot video question answering via frozen bidirectional language models. Advances in Neural Information Processing Systems, 35:124–141, 2022. 1
- [66] Antoine Yang, Arsha Nagrani, Paul Hongsuck Seo, Antoine Miech, Jordi Pont-Tuset, Ivan Laptev, Josef Sivic, and Cordelia Schmid. Vid2seq: Large-scale pretraining of a visual language model for dense video captioning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 10714–10726, 2023. 1
- [67] Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. Activitynet-qa: A dataset for understanding complex web videos via question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 9127–9134, 2019. 2
- [68] Jeffrey M Zacks, Nicole K Speer, Khena M Swallow, Todd S Braver, and Jeremy R Reynolds. Event perception: a mindbrain perspective. *Psychological bulletin*, 133(2):273, 2007.
- [69] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In Proceedings of the IEEE/CVF international conference on computer vision, pages 11975–11986, 2023. 3
- [70] Hang Zhang, Xin Li, and Lidong Bing. Video-llama: An instruction-tuned audio-visual language model for video understanding. *arXiv preprint arXiv:2306.02858*, 2023. 5, 9
- [71] Haoji Zhang, Yiqin Wang, Yansong Tang, Yong Liu, Jiashi Feng, Jifeng Dai, and Xiaojie Jin. Flash-vstream: Memory-based real-time understanding for long video streams. *arXiv* preprint arXiv:2406.08085, 2024. 1, 2, 9
- [72] Peiyuan Zhang, Kaichen Zhang, Bo Li, Guangtao Zeng, Jingkang Yang, Yuanhan Zhang, Ziyue Wang, Haoran Tan, Chunyuan Li, and Ziwei Liu. Long context transfer from

- language to vision. arXiv preprint arXiv:2406.16852, 2024.
- [73] Ruohong Zhang, Liangke Gui, Zhiqing Sun, Yihao Feng, Keyang Xu, Yuanhan Zhang, Di Fu, Chunyuan Li, Alexander Hauptmann, Yonatan Bisk, et al. Direct preference optimization of video large multimodal models from language model reward. arXiv preprint arXiv:2404.01258, 2024. 3
- [74] Ruoyu Zhang, Lulu Wang, Yi He, Tongling Pan, Zhengtao Yu, and Yingna Li. Tpcap: Unlocking zero-shot image captioning with trigger-augmented and multi-modal purification modules. arXiv preprint arXiv:2502.11024, 2025.
- [75] Yue Zhao, Ishan Misra, Philipp Krähenbühl, and Rohit Girdhar. Learning video representations from large language models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 6586– 6597, 2023. 9
- [76] Xingyi Zhou, Anurag Arnab, Shyamal Buch, Shen Yan, Austin Myers, Xuehan Xiong, Arsha Nagrani, and Cordelia Schmid. Streaming dense video captioning. In *Proceedings* of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 18243–18252, 2024. 9